

DEFENSE LOGISTICS AGENCY

DLA LAND AND MARITIME POST OFFICE BOX 3990 COLUMBUS, OH 43218-3990

March 06, 2013

Mr. Dwight Herring AVX Ceramics Division, P.O. Box 867, 801 17th Avenue South, Myrtle Beach, SC 29577-0867

Dear Mr. Dwight Herring,

Re: Notification of Qualification extension, MIL-PRF-55681, FSC 5910, letter # VQP-13-025942, Control # 038684

We have received your email dated February 26, 2013 along with your request for qualification extension of terminal finish Z, in MIL-PRF-55681 to your existing listings. After review your request was found to meet the requirements of the subject military specification and is approved for Qualified Products List (QPL) 55681. The next revision of QPL-55681 will reflect addition of the Z termination finish:

| Government Designation | Manufacturer's Designation | Test or Qualification Reference | Manufacturer's Name and Address |
|---|----------------------------|------------------------------------|--|
| CDR01 10 pF thru 4700 pF; tols. J, K, M; in 50, 100 volts; BP, BX rated temp. and volt. temp. limits; term. M, N, S, U, W, Y, Z; life failure rate M, P, R, S | 805-CDR01 | 55681-399-79 | AVX 801 17th Avenue South, Myrtle Beach, SC 29577-0867 |
| CDR02 220 pF thru 22000 pF; tols. J, K, M; in 50, 100 volts; BP, BX rated temp. and volt. temp. limits; term. M, N, S, U, W, Y, Z; life failure rate M, P, R, S | 1805-CDR02 | 55681-399-79 | AVX 801 17th Avenue South, Myrtle Beach, SC 29577-0867 |
| CDR03 330 pF thru 68900 pF; tols. J, K, M; in 50, 100 volts; BP, BX rated temp. and volt. temp. limits; term. M, N, S, U, W, Y, Z; life failure rate M, P, R, S | 1808-CDR03 | 55681-399-79 | AVX 801 17th Avenue South, Myrtle Beach, SC 29577-0867 |

| Government Designation | Manufacturer's Designation | Test or Qualification Reference | Manufacturer's Name and Address |
|---|----------------------------|------------------------------------|---|
| CDR04 1200 pF thru 180000 pF; tols. J, K, M; in 50, 100 volts; BP, BX rated temp. and volt. temp. limits; term. M, N, S, U, W, Y, Z; life failure rate M, P, R, S | 1812-CDR04 | 55681-400-79 | AVX 801 17th Avenue South, Myrtle Beach, SC 29577-086 |
| CDR05 3900 pF thru 330000 pF; tols. J, K, M; in 50, 100 volts; BP, BX rated temp. and volt. temp. limits; term. M, N, S, U, W, Y, Z; life failure rate M, P, R, S | 1825-CDR05 | 55681-400-79 | AVX 801 17th Avenue South, Myrtle Beach, SC 29577-086 |
| CDR06 6800 pF thru 470000 pF; tols. J, K, M; in 50, 100 volts; BP, BX rated temp. and volt. temp. limits; term. M, N, S, U, W, Y, Z; life failure rate M, P, R, S | 2225-CDR06 | 55681-401-79 | AVX 801 17th Avenue South, Myrtle Beach, SC 29577-080 |
| CDR012 .1 pF thru 1000 pF; tols. B,C,D,F,G,J, K, M; in 50 volts; BG, BP rated temp. and volt. temp. limits; term.S, U, W, Y, Z; life failure rate M, P, R, S | AQ12 | 55681-850-85 | AVX 801 17th Avenue South, Myrtle Beach, SC 29577-086 |
| CDR014 .1 pF thru 5100 pF; tols. B,C,D,F,G,J, K, M; in 50, 100, 200, 300, 500 volts; BG, BP rated temp. and volt. temp. limits; term. S, U, W, Y, Z; life failure rate M, P, R, S | AQ14 | 55681-852-85 | AVX 801 17th Avenue South, Myrtle Beach, SC 29577-086 |

A detailed listing of the capacitor type under the Military Specification Sheet will be listed on the QPL-55681. This qualification is subject to the conditions stated in DoD 4120.24-M and SD-6.

Because we are held responsible for the accuracy and currency of this QPL, please let us know if your company discontinues production of the products listed above. No changes are to be made in the design and construction of the products qualified without approval of the DLA Land and Maritime.

If you have any questions concerning the contents of this letter Please contact Ms. Ami Chase at email: ami.chase@dla.mil or phone: (614) 692-2063.

Sincerely,

/SIGNED/

JOSEPH GEMPERLINE Chief Sourcing and Qualifications Division